

# HS

## *Oil-Heated, Hot Water Generator That Attaches to a Cold Water Pressure Washer*

- Up to 3000 PSI
- Increases incoming water temperature by up to 150°F
- Schedule 80 Heating Coil
- Tubed Pneumatic Tires

### HOW IT IS USED

The HS-3000 is an electric-powered, diesel/oil-heated hot water generator that attaches to a cold-water pressure washer essentially turning it into a hot water pressure washer.

The HS-3000 does not have a pump but simply heats the pressurized water—as much as 150°F above the water's ambient temperature, depending on the flow rate so it can be used for cleaning the toughest of cleaning challenges.

Even though it is more like an accessory, the HS-3000 is packed with all of the quality components that have established the built-to-last reputation of our equipment, including Schedule 80 heating coil, tubed pneumatic tires, and high-efficiency burner.



■ Extra-durable **Heating Coil** made of leak-free, cold-rolled, Schedule 80 steel pipe with five-year warranty.

■ Rust-free, 11-gallon **Fuel Tank** with elevated fuel line to prevent dirt and debris from reaching burner.

■ Helpful **Tri-Lingual Labels** with operating instructions in English, Spanish and French for owner and operator protection.

■ Rugged 12-gauge steel **Chassis** protected by weather-resistant epoxy powder coat paint.

■ 9 feet of wire-braid **Hose** with coupler for connecting to a cold water pressure washer.

■ **Triple Safety Protection**, including a rupture disk, high-limit thermostat and flow switch to prevent the buildup of excessive pressures or heat.

■ High-efficiency **SureFire Burner** is easy to access and is protected by coil wrap hood.

■ 36 feet of high-grade **Electrical Cord** with **Ground Fault Circuit Interrupter** for operator safety.

■ Two-ply, tubed **Pneumatic Tires** make for easy maneuvering in any terrain.



| Model # | Part #      | GPM     | PSI  | Volts | Phase | Amps | BTUs    | Ship Wt (lbs) |
|---------|-------------|---------|------|-------|-------|------|---------|---------------|
| HS-3000 | 1.103-900.0 | up to 6 | 3000 | 120   | 1     | 5    | 420,000 | 425           |



### Field Installed Options & Accessories

|             |            |                                 |
|-------------|------------|---------------------------------|
| 9.804-067.0 | 4-02755030 | E-Zee Hose Reel (100' capacity) |
| 8.903-522.0 | 30-5022    | E-Zee Hose Reel Mounting Kit    |
| 8.903-530.0 | 30-512     | Stainless Steel Outer Wrap ♦    |

♦ Factory Installed

# NG

## Natural Gas-Heated, Hot Water Generator That Attaches to a Cold Water Pressure Washer

- Up to 3000 PSI
- Increases incoming water temperature by up to 150°F
- Schedule 80 Heating Coil
- LP Conversion Option

### Why Choose the NG Hot Water Generator

The NG-3000 is a stationary, natural gas-heated hot water generator that can be attached to a cold-water pressure washer making it a hot water washer.

The NG-3000 does not have a pump but simply heats the pressurized water—as much as 150°F above the water's ambient temperature, depending on the flow rate—so it can be used for cleaning the toughest of cleaning challenges.

There are two models—NG-3000 and NG-3000LM—able to heat water at flow rates of up to 10.6 GPM. Both models can be converted to LP gas.

The NG models are packed with quality throughout, including Schedule 80 heating coil, high-efficiency burner, rugged steel frame and a raised platform for easy positioning in a shop.



**NG-3000LM**  
Shown with optional support table

**NG-3000**

- **Extra-durable Heating Coil** made of leak-free, cold-rolled, Schedule 80 steel pipe with five-year warranty.
- **Rugged 12-gauge steel Chassis** protected by weather-resistant epoxy powder coat paint.
- **Triple Safety Protection**, including a rupture disk, high-limit thermostat, and flow switch to prevent the buildup of excessive pressures or heat.
- **High-efficiency Burner** with millivolt ignition and standing pilot; also Honeywell gas valve.

■ **Helpful Tri-Lingual Labels** with operating instructions in English, Spanish and French for owner and operator protection.

■ **9 feet of wire-braid Hose** with coupler for connecting to a cold water pressure washer.



| Model #   | Part #      | Fuel        | GPM        | PSI  | Max BTUs | Ship Wt (lbs) |
|-----------|-------------|-------------|------------|------|----------|---------------|
| NG-3000   | 1.103-901.0 | Natural Gas | Up to 6    | 3000 | 420,000  | 450           |
| NG-3000LM | 1.103-902.0 | Natural Gas | Up to 10.6 | 3000 | 800,000  | 900           |

**Distributed by:**

#### Field Installed Options & Accessories

|             |             |                                     |
|-------------|-------------|-------------------------------------|
| 9.801-042.0 | 35-211      | LP Conversion Kit (for NG-3000) ♦   |
| 8.904-068.0 | 35-212      | LP Conversion Kit (for NG-3000LM) ♦ |
| 9.802-633.0 | 7-1010      | LP Regulator Assembly               |
| 9.801-040.0 | 7-10031     | Draft Diverter, 10" (NG-3000)       |
| 8.717-730.0 | 7-10032     | Draft Diverter, 12" (NG-3000LM)     |
| 8.912-689.0 | 95-07163653 | Support Table, 8" (for NG-3000LM)   |

♦ Factory Installed